



XI'AN FUNCTION MATERIAL GROUP CO., LTD
Safety Data Sheet
Barium Niobium Oxide

1. Product and Company Identification

Trade Name:	Barium niobium oxide
Chemical Formula:	BaNb ₂ O ₆
Recommended Use:	Scientific research and development
Manufacturer/Supplier:	XI'AN FUNCTION MATERIAL GROUP CO., LTD
Street:	No. 69, Gazelle Valley, High-Tech Zone
City:	XIAN
State:	SHAANXI
Zip Code:	710077
Country:	CHINA
Tel #:	+86-29-88993870/+86-13519132051

2. Hazards Identification

Signal Word: Warning



Hazard Statements: H302+H332: Harmful if swallowed or if inhaled

Precautionary Statements: P261 Avoid breathing dust/fume/vapor
P264: Wash thoroughly after handling.
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P312: Call a POISON CENTER or doctor/physician if you feel unwell
P501: Dispose of contents/container in accordance with local/regional/national/international regulations

HMIS Health Ratings (0-4):

Health:	2
Flammability:	0
Physical:	1

3. Composition

Chemical Family: Ceramic
Additional Names: Barium niobate

Barium niobium oxide (BaNb₂O₆):
Percentage: 100 wt%
CAS #: 12009-14-2
EC #: N/A

4. First Aid Procedures

General Treatment: Seek medical attention if symptoms persist.
Special Treatment: None
Important Symptoms: None

Inhalation: Remove victim to fresh air. Supply oxygen if breathing is difficult.
Ingestion: Seek medical attention.
Skin: Wash affected area with mild soap and water.
Eyes: Flush eyes with water, blinking often for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

5. Firefighting Measures

Flammability: Non-flammable
Extinguishing Media: No special restrictions – use suitable extinguishing agent for surrounding material and type of fire.
Spec. Fire Fighting Procedure: Use full-face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. See section 10 for decomposition products.

6. Accidental Release Measures

If Material Is Released/Spilled: Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust.
Environmental Precautions: Isolate runoff to prevent environmental pollution.

7. Handling and Storage

Handling Conditions: Wash thoroughly after handling.
Storage Conditions: Store in a cool dry place in a tightly sealed container. Store apart from materials and conditions listed in section 10.
Work/Hygienic Maintenance: Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.
Ventilation: Provide sufficient ventilation to maintain concentration at or below threshold limit.

8. Exposure Controls and Personal Protection

Permissible Exposure Limits:	0.5 mg/m ³ as Ba, long-term value
Threshold Limit Value:	0.5 mg/m ³ as Ba, long-term value
Special Equipment:	None
Respiratory Protection:	Dust Respirator
Protective Gloves:	Rubber gloves
Eye Protection:	Safety glasses or goggles
Body Protection:	Protective work clothing. Wear close-toed shoes and long sleeves/pants.

9. Physical and Chemical Characteristics

Color	Off-white
Form:	Powder
Odor:	Odorless
Water Solubility:	Insoluble
Boiling Point:	N/A
Melting Point:	N/A
Flash Point:	N/A
Autoignition Temperature:	N/A
Density:	N/A
Molecular weight:	419.134 g/mol

10. Reactivity

Stability:	Stable under recommended storage conditions
Reacts With:	Oxidizing agents
Incompatible Conditions:	None
Hazardous Decomposition Products:	Barium oxide

11. Toxicological Information

Potential Health Effects:	
Eyes:	Causes irritation
Skin:	Causes irritation
Ingestion:	Harmful
Inhalation:	Harmful
Chronic:	Barium compounds may cause severe gastroenteritis, including abdominal pain, vomiting and diarrhea, tremors, faintness, paralysis of the arms and legs, and slow or irregular heartbeat. Severe cases may produce collapse and death due to respiratory failure, soluble barium compounds are more likely to cause the effects than insoluble compounds. Inhalation of fumes may cause sore throat, coughing, labored breathing, and irritation of the respiratory tract as well as the above symptoms. Niobium compounds have caused liver damage in animal studies. Niobium metal has caused kidney damage in laboratory animals via intravenous route and fibrogenic effects in laboratory animals via intratracheal route.
Signs & Symptoms:	N/A
Aggravated Medical Conditions:	N/A
Median Lethal Dose:	N/A
Carcinogen:	N/A

12. Ecological Information

Aquatic Toxicity:	Low
Persistent Bioaccumulation Toxicity:	No
Very Persistent, Very Bioaccumulative:	No
Notes:	N/A

13. Disposal Considerations

Dispose of in accordance with local, state, national, and international regulations.

14. Transportation Data

Hazardous:	Hazardous.
------------	------------



Hazard Class:	6.1 Toxic substances.
Packing Group:	III
UN Number:	UN1564
Proper Shipping Name:	Barium compounds, n.o.s. (Barium niobium oxide)

15. Regulatory Information

Sec 302 Extremely Hazardous:	No
Sec 304 Reportable Quantities:	N/A
Sec 313 Toxic Chemicals:	Yes

16. Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised: 06/16/2015